



MARLUVAS

PROFESSIONAL EQUIPMENT

Vulcaflex Line

10VT48 A

Safety shoe with steel toe cap, entire upper, padded collars, made of leather, side elastic closure, internal lining and dual density sole.



Technical Specifications:

- Steel toe cap
- Padded collars
- Entire upper
- Relax leather upper
- Internal lining
- Antibacterial hygienic insole
- PU dual density sole



Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 0,9g/cm³, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and resistant to slipping on ceramic and steel floors (SRC Level).



Uppers: Black relax leather from 15 to 17 lines thick

Trinforcement: Termoplastic 1,5mm thick

Tread: Polyamide nº 30.

Standard: NBR ISO 20345:2015

Sizes: From 33 to 47

Warranty: 36 months

Color: Black

Approval Certificate: 43341

Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap: 1045 carbon steel impact resistance up to 200J, 1,5mm thick and anticorrosive electrostatic painting

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Upper sewed by strobels system, resin and needle-polyester - 2,0mm thick

Single shoe weight: 0,398kg

Height leg: 80mm

Obs.: height leg is based on size 40 and it may vary 3,33 mm per size.

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

Technologies



woven made of polyester fibers that ensure greater softness, lightness and convenience to users

Segmentos



Production Area



General Services



Service Providers



Utility Workers

Note: warranty begins from the date of production of the shoe