

London Safe Line

20S29 BS T

Cód. Comercial: 700601 – CA 33698

Occupational boot with plastic toe cap, made of leather, lace closure and side protection, internal lining, and dual-density sole.



Applications



Administrative Areas



General Services

Footwear construction

Sole Composed of two layers of polyurethane (P.U.), directly injected into the upper: the first layer (midsole) is softer and lighter, with a density of 0.4g/cm³, providing greater comfort; and the 2nd layer (outsole) is more compact with a density of 0.9 g/cm³, resistant to abrasion with an anti-slip system, consisting of special grooves 3mm high and 6mm wide, and slip resistance on ceramic and steel floors (SRC level).

Upper Smooth vaqueta leather with a thickness of 14 to 16 lines.

Thermoplastic Counter 1.5mm

Polyamide thread No. 30.

Vamp and Sweatband Lining Intelligent moisture dispersal and temperature thermoregulation system, with a coating of microcapsules PCM Outlast Climatech.

True-line toe cap Citoplastic activated at 200°C, applied hot by fusion to the vamp, thickness of 0.9mm.

Anatomical Hygienic Insole Made of Rubber E.V.A. anti-fungal/antibacterial, composed of microdots that provide sweat absorption and desorption.

Assembly Insole Stitched to the upper using the Strobel system, made of needled and resin-coated polyester, with a thickness of 2.0mm.

Color Black

Sizes 33 to 47

Technical Information

Standard NBR ISO 20347:2015

Shelf Life 36 months

Note: The shelf life of the equipment begins from the manufacturing date engraved on the footwear

Weight per shoe 0.457kg

Boot Shaft Height 110mm

Note: height leg is based on size 40 and it may vary 3,33 mm per size

Packaging

Size: L 310mm x D 175mm x H 110mm (Individual box)

Sizes: L 565mm x D 300mm x H 245mm (Collective box for up to 5 pairs)

Sizes: L 414mm x D 315mm x H 505mm (Collective box for up to 10 pairs)

[For information about shoes warranty click here](#)

marluvas.com.br
0300 788 3323

