



MARLUVAS

PROFESSIONAL EQUIPMENT

Prime Line

50B19 A MEX

Safety boot with steel toe cap, made of leather, side elastic closure, internal lining, metatarsal protection and dual density sole.



Technical Specifications:

- Steel toe cap
- relax leather uppers
- Internal lining
- Antibacterial hygienic insole
- External polypropylene metatarsal protection
- PU dual density sole with electrical resistant

Uppers: Relax cowhide leather from 15 to 17 lines thick

Trinforcement: Termoplastic 1,5mm thick

Tread: Polyamide nº 30.

Standard: NBR ISO 20345:2015

Sizes: From 33 to 47

Warranty: 36 months

Color: Black

Approval Certificate: 43274



Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 0,9g/cm³, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and 600V electrical resistant and top cap covering.



Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap: 1045 carbon steel impact resistance up to 200J, 1,5mm thick and anticorrosive electrostatic painting

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Upper sewed by strobel system, resin and needle-polyester - 2,0mm thick

Single shoe weight: 0,527kg

Height leg: 120mm

Obs.: height leg is based on size 40 and it may vary 3,33 mm per size.

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

Technologies



Hygienic insole with antibacterial properties composed of EVA and micro-stitches providing sweat absorption and desorption.

Segmentos



Eletrical



Agrobusiness



Agricultural



Logging business

Note: warranty begins from the date of production of the shoe