

Prime Line

50B19-MIN-A-PA-CP

Cód. Comercial: 700028 – CA: 17414

Safety boot with steel toe cap and protective cover, made of leather, with elastic side closure, internal metatarsal protector, internal lining, dual-density sole and steel insole resistant to perforation.




Segments



Agriculture



Agroindustry



Wood Industry

Construcción del Calzado

Outsole: Composed of two layers of polyurethane (PU), injected directly onto the upper. The 1st layer (midsole) is softer and lighter, with a density of 0.4 g/cm³, providing greater comfort; the 2nd layer (outsole) is more compact, with a density of 1.0 g/cm³, abrasion-resistant, featuring an anti-slip design with special grooves 3 mm high and 6 mm wide, ensuring slip resistance on ceramic and steel floors (SRC Level).

Upper: Relaxed grain leather, thickness from 1.5 to 1.7 lines.

Color: Black.

Sizing: PU/Rubber bi-density – sizes 33 to 47.

Toe cap lining and vamp: Non-woven short fiber fabric with a minimum thickness of 1.9 mm.

Toe cap: Carbon steel 1045, resistant to impacts of 200 J, with 1.5 mm thickness and anti-corrosive electrostatic paint.

Steel Insole: Made of stainless steel, puncture-resistant, withstanding forces of up to 110 kg, providing effective protection against perforation.

Hygienic Insole: Anatomically shaped EVA, black, composed of micro-points that provide sweat absorption and desorption.

Información Técnica

Requirement: NBR ISO 20345:2015

Validity: 36 months – the validity period starts from the manufacturing date stamped on the footwear.

Weight per foot: 0.577 kg

Shaft height: 116 mm

(Note: Shaft height is based on size 40 footwear and may vary by 5.33 mm per size.)

Packaging

- Dimensions: L 565 mm x W 300 mm x H 245 mm
- (Collective box for up to 5 pairs)
- Dimensions: L 414 mm x W 315 mm x H 505 mm
- (Collective box for up to 10 pairs)

For information about footwear warranty, [click here.](#)