



# MARLUVAS

PROFESSIONAL EQUIPMENT

## Trekking Line

### 50B26 CB C NUB

Safety boot with composite toe cap, padded collars, made of leather, lace closure, internal lining and dual density sole.



### Technical Specification:

- Composite toe cap
- Nubuck leather uppers
- Padded collars
- internal lining
- Antibacterial hygienic insole
- PU dual density sole

**Sole:** Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm<sup>3</sup>, providing more comfort; and more compact sole (second layer) – density 0,9g/cm<sup>3</sup>, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and resistant to slipping on ceramic and steel floors (SRC Level).



**Uppers:** Nubuck leather from 15 to 17 lines thick

**Trinforcement:** Termoplastic 1,5mm thick

**Tread:** Polyamide nº 30.

**Standard:** NBR ISSO 20345:2015

**Sizes:** From 33 to 47.

**Warranty:** 36 months

**Color:** Coffee Brown / Black

**Approval Certificate** 42393

**Upper and strap Lining:** Non-woven in short fibers with a minimum 1,9 thickness.

**Toe cap:** Ultra-resilient polymer, withstanding 200J impact and compression up to 1500Kg (N) and 51% lighter than steel toe caps. It also has antimagnetic and anti-corrosive properties besides being undetectable by metal detectors.

**Hygienic Insole:** Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

**Assembly insole:** Upper sewed by strobel system, resin and needle-polyester - 2,0mm thick

**Single shoe weight:** 0,458kg

**Height leg:** 125mm  
Obs: height leg is based on size 40 and it may vary 3,33 mm per size.

**Product Package**  
- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)  
- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

### Technologies



Air confort woven made of polyester fibers that ensure greater softness, lightness and convenience to users



Hygienic insole with antibacterial properties composed of EVA and micro-stitches providing sweat absorption and desorption.



Composite TOE Comfortable, lightweight and impact-resistant composite non-metallic toe cap. withstanding 200J impact and compression up to 1500 N according to NBR ISO 20345/2015.

### Segmentos



Production Area



General Services



Civil Constructions

Note: warranty begins from the date of production of the shoe