



MARLUVAS

PROFESSIONAL EQUIPMENT

Trekking Line

50B26 CPAP NUB

Safety boot with composite toe cap, padded collars, made of cut resistant leather (CR), lace closure, metallic free components, internal lining and dual density sole.



Technical Specification:

Composite toe cap

Nubuck leather uppers

Padded collars

internal lining

Antiperforation assembly insole

Antibacterial hygienic insole

PU dual density sole

Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 0,9g/cm³, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and resistant to slipping on ceramic and steel floors (SRC Level).



Uppers: Nubuck leather from 15 to 17 lines thick

Trinforcement: Termoplastic 1,5mm thick

Tread: Polyamide nº 30.

Standard: NBR ISSO 20345:2015

Sizes: From 33 to 47.

Warranty: 36 months

Color: Coffee Brown / Black

Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap: Ultra-resilient polymer, withstanding 200J impact and compression up to 1500Kg (N) and 51% lighter than steel toe caps. It also has antimagnetic and anti-corrosive properties besides being undetectable by metal detectors.

Note: Class I insulating footwear has the purpose of insulation in low voltage electrical installations up to 500 V in dry conditions. The shoe is submitted to a test voltage of 14,000V or 14kv to have its properties checked (the leakage current is verified)

Approval Certificate 33111

Single shoe weight: 0,503kg

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Height leg: 117mm

Obs: height leg is based on size 40 and it may vary 3,33 mm per size.

Assembly insole: Non-metallic perforation resistant up to 1100N, made in multiple layers in fiber 100% polyester. Protecting all the plantar surface of the feet.

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

Technologies



Air confort woven made of polyester fibers that ensure greater softness, lightness and convenience to users



PAP Puncture-resistant, lightweight, non-metallic aramid fiber insole that covers 100% of the sole. Resistant to minimum drilling of 1100N according to NBR ISO 20344: 2015.



Composite TOE Comfortable, lightweight and impact-resistant composite non-metallic toe cap. withstanding 200J impact and compression up to 1500 N according to NBR ISO 20345/2015.

Segmentos



Production Area



General Services



Civil Constructions



Electrical

Note: warranty begins from the date of production of the shoe