

Line Kombat

50C32-CPAP

Cód. Comercial: 700613 - C.A:18059

Safety boot with composite toe cap, made of water-repellent leather, with lace-up closure, internal lining, and dual-density outsole.



Segments



Production Area



Construction



General Services



Electrical Sector

Footwear Construction

Sole: Made of two layers of polyurethane (PU), directly injected onto the upper. The first layer (midsole) is softer and lighter, with a density of 0.4 g/cm³, providing greater comfort; and the second layer (outsole) is more compact, with a density of 0.9 g/cm³, abrasion-resistant, and features an anti-slip system with special grooves 3 mm high and 6 mm wide.

Water-repellent vaqueta-type leather, thickness 15 to 17 stitches (lines).

Color: black

Size range: 33 to 47.

Vamp and quarter lining: non-woven short-fiber fabric with a minimum thickness of 1.9 mm.

Counter: 1.5 mm thermoplastic.

Toe cap: ultra-resistant polymer material, withstands impacts of 200 J and compression of 1500 kgf (N), approximately 51% lighter than steel toe caps. Features anti-magnetic and anti-corrosive properties and is non-detectable by metal detectors.

Insole board: non-metallic, made of multiple layers of 100% polyester fibers. Puncture resistant up to 1100 N, protecting 100% of the plantar surface of the foot.

Note: Safety footwear approved according to NBR ISO 20344:2015 standard in puncture resistance tests, providing protection against sharp objects with a diameter greater than 4 mm.

Hygienic insole: anatomical EVA, shaped, composed of micro-dots that provide absorption and desorption of perspiration.

Technical Specifications

Approval: NBR ISO 20345:2015 / NBR 16603:2017.

Note: Class I insulating footwear is designed to provide insulation in low-voltage electrical installations up to 500 V, under dry conditions. The test voltage of 14,000 V (14 kV) is the voltage under which the footwear is tested to verify its insulating properties (leakage current).

Validity in use: 36 months

Note: The validity period of the equipment begins from the manufacturing date engraved on the footwear.

Weight per shoe: 0.675 kg

Boot height: 220 mm

Obs.: The boot height is based on size 40 footwear and may vary by 3.33 mm per size.

Packaging

Sizes: C 34 mm x L 28 mm x A 13 mm (Individual box)

Sizes: C 345 mm x L 593 mm x A 536 mm (Collective box for up to 14 pairs)

For information about footwear warranty, [click here](#).

marluvas.com.br
+55 (32) 3693-4000