



# MARLUVAS

PROFESSIONAL EQUIPMENT

## Pró-Alimentícia Line

### 50C32 FRI BP CP

Safety boot with polypropylene toe cap, made of leather, velcro closure, internal lining and dual density sole.



### Technical Specification

- Polypropylene toe cap
- Cowhide waterproof leather uppers
- Synthetic wool internal lining
- Antibacterial hygienic insole
- PU dual density sole

**Sole:** Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm<sup>3</sup>, providing more comfort; and more compact sole (second layer) – density 0,9g/cm<sup>3</sup>, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and resistant to slipping on ceramic and steel floors (SRC Level).



**Uppers:** Cowhide waterproof leather from 15 to 17 lines thick

**Trinforcement:** Termoplastic 1,5mm thick

**Tread:** Polyamide nº 30.

**Standart:** NBR ISO 20347:2015.

**PU bidensity number:** 35 to 47

**Warranty:** 36 months

**Color:** White

**Approval Certificate:** 13145

**Upper and Strap Lining:** Non-woven in short fibers with a minimum 1,9 thickness.

**Toe cap:** Polypropylene injected plastic, 1,5mm thick. P.S: this kind of toe cap does not have the same safety properties of the the steel cap.

### Segmentos



Food Industry



Meat Locker

**Hygienic Insole:** Anatomically conform in EVA antifungal/ antibacterial, made up of micro-stitches providing sweat absorption and desorption.

**Assembly insole:** Upper sewed by strobel system, resin and needle-polyester - 2,0mm thick

**Single shoe weight:** 0,559kg

**Height Leg:** 175mm

Note: height leg is based on size 40 and it may vary 3,33mm per size.

### Product Package

Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

### Tecnologia



Hygienic insole with antibacterial properties composed of EVA and micro-stitches providing sweat absorption and desorption.



leather with a special treatment making the boot resistant to water penetration according to NBR ISO 20345:2015 standard.



Insulating insole coated with aluminum and thermal interlaced fibers, protecting the feet from heat and cold.

Note: warranty begins from the date of production of the shoe

For more Information about the warranty access our website [marluvas.com.br/garantias](http://marluvas.com.br/garantias)