

Kombat Line

50C32 MAT CPAP

Cód. Comercial: 700843 – CA 45802

Safety boot made of leather, suitable for agrobusiness and military professionals. With non-metallic components (answers NR10).



Applications



Agro Industry



Industrial Eletrician



Military

Footwear construction

Sole Consists of two layers of polyurethane (PU), directly injected into the upper, with the 1st layer (midsole) being softer and lighter, with a density of 0.4g/cm³ for greater comfort; and the 2nd layer (outsole) more compact with a density of 0.9 g/cm³, resistant to cutting, piercing objects, and abrasion, with an anti-slip system consisting of special 3mm high and 6mm wide grooves.

Upper Leather, smooth vaqueta type, with a thickness of 18 lines to 20 lines.

Thermoplastic counter with a thickness of 1.5mm.

Polyamide stitching No. 30.

Vamp and Sweatband Lining Non-woven fabric with a minimum thickness of 1.9mm.

Composite Toe Cap Ultra-Resistant capable of withstanding impacts of 200J and compression of up to 1500Kg (N), and lighter by up to about 51% compared to steel toe caps. It also has antimagnetic and anticorrosive properties, and is undetectable by metal detectors.

Hygienic insole Soft Comfort made of antifungal/antibacterial EVA, composed of microdots that provide sweat absorption and desorption.

Puncture-resistant insole Non-metallic, withstands up to 1100N of force, made of multiple layers of 100% polyester fibers. Protects the entire plantar surface of the foot.

Color Black

Sizes 33 to 47.

Technical Information

Standard NBR ISO 20345:2011

Shelf Life 36 months

Note: The shelf life of the equipment begins from the manufacturing date engraved on the footwear

Weight per shoe 0.694kg

Boot Shaft Height 42.6cm

Note: height leg is based on size 40 and it may vary 3,33 mm per size

Packaging

Sizes: L 345mm x W 595mm x H 536mm (Collective box for up to 14 pairs)

Sizes: L 565mm x W 300mm x H 245mm (Collective box for up to 5 pairs)

[For information about shoes warranty click here](#)

marluvas.com.br
0300 788 3323

