



MARLUVAS

PROFESSIONAL EQUIPMENT

Trekking Line

50S29 NUB

Safety shoe with polypropylene toe cap, padded collars, made of leather, lace closure, internal lining and dual density sole.



Technical Specification:

Polypropylene toe cap

Nubuck leather uppers

Padded collars

internal lining

Antibacterial hygienic insole

PU dual density sole

Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 0,9g/cm³, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and resistant to slipping on ceramic and steel floors (SRC Level).

Uppers: Nubuck leather from 15 to 17 lines thick

Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap: 1045 carbon steel impact resistance up to 200J, 1,5mm thick and anticorrosive electrostatic painting.

Trinforcement: Termoplastic 1,5mm thick

Tread: Polyamide nº 30.

Standard: NBR ISSO 20347:2015

Sizes: From 33 to 47.

Warranty: 36 months

Color: Coffee Brown

Approval Certificate 15303

Single shoe weight: 0,346kg

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Height leg: 72mm
Obs: height leg is based on size 40 and it may vary 3,33 mm per size.

Assembly insole: Upper sewed by strobels system, resin and needle-polyester - 2,0mm thick

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)
- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

Technologies



Air confort woven made of polyester fibers that ensure greater softness, lightness and convenience to users

Segmentos



Production Area



General Services



Civil Constructions

Note: warranty begins from the date of production of the shoe