

New Prime Line

50T19 BP

Cód. Comercial: 700110 – CA 44350

Occupational shoe with plastic toe cap, padded collar, made of vaqueta leather, side elastic closure, internal lining, and dual-density sole.



Applications



Administrative Areas



General Services



Production Areas

Tecnologies



Hygienic insole with antibacterial properties, composed of EVA and micropoints that provide sweat absorption and desorption.



Fabric composed of polyester fibers that guarantee greater softness, lightness, and comfort for users.

Footwear construction

Sole Consisting of two layers of polyurethane (PU), injected directly into the upper, with the 1st layer (midsole) softer and lighter, with a density of 0.4g/cm³ for greater comfort; and the 2nd layer (sole) denser with a density of 0.9g/cm³, resistant to sharp objects, punctures, and abrasion, with an anti-slip system consisting of special grooves, 3mm high and 6mm wide.

Thermoplastic Counter 1.5mm

Polyamide Thread No. 30

Lining Fabric and Sweating Non-woven short-fiber fabric with a minimum thickness of 1.9mm.

Plastic toe cap injected in polypropylene, with a thickness of 1.5mm. Note: this type of toe cap does not have the same safety characteristics as a steel toe cap.

Stitched insole attached to the upper by the Strobel system, made of needled and resin-coated polyester with a thickness of 2.0mm.

Color White

Sizes Dual-Density PU 33 to 47

Technical Information

Standard NBR ISO 20347:2015.

Validity 36 months

Note: The shelf life of the equipment begins from the manufacturing date engraved on the footwear

Weight per shoe 0.564kg

Boot Shaft Height 88mm

Note: height leg is based on size 40 and it may vary 3,33 mm per size

Packaging

Plastic bag in collective boxes

Sizes: L 565mm x W 300mm x H 245mm (Collective box for up to 5 pairs)

Sizes: L 414mm x W 315mm x H 505mm (Collective box for up to 10 pairs)

[For information about shoes warranty click here](#)

marluvas.com.br
0300 788 3323

