



MARLUVAS

PROFESSIONAL EQUIPMENT

Têmpera Line

60B19

Safety boot with polypropylene toe cap, padded collars, made of leather, side elastic closure, internal lining and bicomponent sole.



Technical Specification

- Polypropylene toe cap
- Cowhide leather uppers
- Padded collars
- Internal lining
- Antibacterial hygienic insole
- PU/rubber sole



Sole: : Made of two layers of polyurethane (PU)/nitrile rubber, directly injected in the upper, softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 1,05 g/cm³, abrasion resistant with antislip system made up of special grooves, 3mm height and 6mm width and resistance to 300°C warmth for up to a minute(HRO) and resistant to ceramic and steel surface (level SRC).



Uppers: Cowhide relax leather from 15 to 17 lines thick

Trinforcement: Termoplastic 1,5mm thick

Tread: Polyamide nº 30.

Standard: NBR ISO 20347:2015

Sizes: From 33 to 47.

Warranty: 36 months

Color: Black

Approval Certificate: 18061

Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap: Polypropylene injected plastic, 1,5mm thick. P.S: this kind of toe cap does not have the same safety properties of the the steel cap.

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Upper sewed by strobel system, resin and needle-polyester - 2,0mm thick

Single shoe weight: 0,400kg

Height leg: 114mm

Obs.: height leg is based on size 40 and it may vary 3,33 mm per size.

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

Technologies



Hygienic insole with antibacterial properties composed with EVA and micro points that provide sweat absorption and desorption.

Segmentos



Agricultural



Siderurgy



Metallurgy



Paving

Note: warranty begins from the date of production of the shoe