

Kombat Line

60C32 MT A MEX

Cód. Comercial: 700171 – CA 37533

Occupational boot with plastic toe cap, made of leather, lace closure, internal lining, side protection, and dual-density sole.



Applications



Agro Industry



Siderurgy



Logging

Footwear construction

Sole Consists of two layers of polyurethane (PU)/nitrile rubber, directly injected into the upper, with the 1st layer (midsole) being softer and lighter, with a density of 0.4g/cm³ for greater comfort; and the 2nd layer (outsole) more compact with a density of 1.05 g/cm³, resistant to cutting, piercing objects, and abrasion, with a special groove system 3mm high and 6mm wide and resistance to direct heat contact up to 300°C for up to one minute.

Upper Relax vaqueta leather type with a thickness of 18 to 20 lines.

Thermoplastic counter with a thickness of 1.5mm.

Polyamide stitching No. 30.

Vamp and Sweatband Lining Non-woven fabric with a minimum thickness of 1.9mm.

Steel Toe Cap 1045 carbon steel, resistant to 200J impact, with a thickness of 1.5mm and anti-corrosive electrostatic paint.

Assembly insole Stitched to the upper using the Strobel system, made of resin-coated synthetic material with a thickness of 2.0 mm.

Hygienic insole Soft Comfort made of antifungal/antibacterial EVA, composed of microdots that provide sweat absorption and desorption.

Color Black and orange

Sizes 35 to 47

Technical Information

Standard NBR ISO 20345:2015. ISO 17249/2013

Shelf Life 36 months

Note: The shelf life of the equipment begins from the manufacturing date engraved on the footwear

Weight per shoe 0.832kg

Boot Shaft Height 21.9cm

Note: height leg is based on size 40 and it may vary 3,33 mm per size

Packaging

Sizes: L 345mm x W 595mm x H 536mm (Collective box for up to 14 pairs)

Sizes: L 565mm x W 300mm x H 245mm (Collective box for up to 5 pairs)

[For information about shoes warranty click here](#)

marluvas.com.br
0300 788 3323

