



MARLUVAS

PROFESSIONAL EQUIPMENT

Composite Line

70B19 CPAP

Safety boot with composite toe cap, padded collars, made of microfiber, side elastic closure, internal lining and dual density sole.



Especificação Técnica

- Composite toe cap
- MMicro microfiber uppers
- Padded collars
- Internal lining
- Antiperforation assembly insole
- Antibacterial hygienic insole
- PU dual density sole

Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 1,0 g/cm³, abrasion resistant with antislip system made up of special grooves, 3mm height and 6mm width and slip resistance on ceramic steel floor (SRC level)



Uppers: Mmicro microfiber 18 lines thick

Trinforcement: Termoplastic 1,5mm thick

Tread: Nylon nº 30.

Standard: NBR ISO 20345:2015.
NBR 16603/2017

Sizes: From 33 to 47.

Warranty: 36 months

Color: Black

Approval Certificate: 34549

Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap: ultra-resilient polymer, withstanding 200J impact and compression up to 1500Kg (N) and 51% lighter than steel toe caps. It also has antimagnetic and anti-corrosive properties besides being undetectable by metal detectors.

Note: Class I insulating footwear has the purpose of insulation in low voltage electrical installations up to 500 V in dry conditions. The test voltage which is 14,000 V or 14 KV is the voltage under which the footwear is subjected to verification of its properties (the leakage current is verified).

Single shoe weight: 0,460kg

Height leg: 117mm

Obs.: height leg is based on size 40 and it may vary 3,33 mm per size.

Hygienic Insole: Anatomically conform in EVA antifungal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Non-metallic perforation resistant up to 1100N, made in multiple layers in fiber 100% polyester. Protecting all the plantar surface of the feet.

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

Technologies



Air confort woven made of polyester fibers that ensure greater softness, lightness and convenience to users



Composite TOE Comfortable, lightweight and impact-resistant composite non-metallic toe cap, withstanding 200J impact and compression up to 1500 N according to NBR ISO 20345/2015.



M MICRO High performance microfiber. Its texture is very similar to leather but it is washable, lighter and chemical resistant



PAP Puncture-resistant, lightweight, non-metallic aramid fiber insole that covers 100% of the sole. Resistant to minimum drilling of 1100N according to NBR ISO 20344: 2015.

Segmentos



Construction



Mechanical



Electrical

Note: warranty begins from the date of production of the shoe