

New Prime Line

70B22 PAZ BP

Commercial Code : 701218 – CA 35768

Occupational boot with plastic toe cap, padded collar, made of microfiber, lace-up closure, non-metallic blue eyelets, internal lining, and bidensity sole



Segmentos



Footwear construction.

Sole: Composed of two layers of polyurethane (PU), injected directly into the upper, with the first layer (midsole) being softer and lighter, with a density of 0.4 g/cm³, providing greater comfort; and the second layer (outsole) more compact with a density of 0.9 g/cm³, abrasion-resistant, featuring an anti-slip system made of special grooves 3 mm in height and 6 mm in width, slip resistance on ceramic and steel floors (SRC level)

Counter: 1.5 mm thermoplastic

Empeine: Confeccionado en microfibra M Micro con un grosor de 17 a 19 hilos

Lining of the upper and sweat area: Non-woven short fiber fabric with a minimum thickness of 1.9 mm

Toe cap: Injection-molded polypropylene, thickness of 1.5 mm.

Note: This type of toe cap does not have the same safety features as the steel toe cap

Hygienic insole: Soft Comfort in antifungal/antibacterial EVA, composed of micropoints that provide sweat absorption and desorption

Insole: Sewn to the upper using the Strobel system, made of carded and resin-treated polyester with a thickness of 2.0 mm

Simple sizing: 33 to 47

Color: Black

Especificação Técnica

Requirement NBR ISO 20345:2015 - NBR 16603/2017

Validity: 36 months

Note : The validity of the equipment begins from the manufacturing date engraved on the footwear

Weight per shoe: 0.400 kg

Shaft height: 160 mm

Note: The shaft height is based on size 40 footwear, with a possible variation of 3.33 mm per size

Packaging

Plastic bag: (450x450 mm) in collective boxes Sizes: L 450 mm x W 325 mm x H 320 mm (Collective box for up to 5 pairs)

[Para informações sobre garantia dos calçados Marluvas CLIQUE AQUI](#)