

Kombat Line

70C32 MAT CA BP

Cód. Comercial: 700271 – CA 36615

Occupational boot with plastic toe cap, made of leather, lace closure, internal lining, side protection, and dual-density sole.



Applications



Agro Industry



Industrial Electrician

Footwear construction

Non-slip sole for improved ground grip, with a quick water dispersion system that prevents debris from accumulating in the grooves. Consists of two layers of polyurethane (PU), directly injected into the upper, with the 1st layer (midsole) being softer and lighter, with a density of 0.4g/cm³ for greater comfort; and the 2nd layer (outsole) more compact with a density of 1.0 g/cm³, resistant to cutting, piercing objects, and abrasion, with an anti-slip system consisting of special 5mm high and 6mm wide grooves.

Upper Made of M Micro microfiber with a thickness of 18 lines.

Thermoplastic counter with a thickness of 1.5mm.

Gray Nylon stitching No. 30.

Vamp and Sweatband Lining Non-woven fabric with a minimum thickness of 1.9mm.

Plastic toe cap Injected in polypropylene, with a thickness of 1.5mm. Note: This type of toe cap does not have the same safety characteristics as a steel toe cap.

Assembly insole Stitched to the upper using the Strobel system, made of resin-coated synthetic material with a thickness of 2.0 mm.

Hygienic insole Soft Comfort made of antifungal/antibacterial EVA, composed of microdots that provide sweat absorption and desorption.

Color Black

Sizes 33 to 47

Technical Information

Standard NBR ISO 20347:2011

Shelf Life 36 months

Note: The shelf life of the equipment begins from the manufacturing date engraved on the footwear

Weight per shoe 0.561kg

Boot Shaft Height 42.6cm

Note: height leg is based on size 40 and it may vary 3,33 mm per size

Packaging

Sizes: L 345mm x W 595mm x H 536mm (Collective box for up to 14 pairs)

Sizes: L 565mm x W 300mm x H 245mm (Collective box for up to 5 pairs)

[For information about shoes warranty click here](#)

marluvas.com.br
0300 788 3323

