



MARLUVAS

PROFESSIONAL EQUIPMENT

Kombat Line

70C32 PET CPAP

Safety boot with composite toe cap, padded collars, made of microfiber, full closing, internal lining and dual density sole.



Technical Specification

- Composite toe cap
- MMicro microfiber uppers
- Padded collars
- Internal lining
- Antiperforation assembly insole
- Antibacterial hygienic insole
- PU dual density sole

Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 1,0 g/cm³, abrasion resistant with antislip system made up of special grooves, 3mm height and 6mm width.



Uppers: Mmicro microfiber 18 lines thick

Trinforcement: termoplastico 1,5mm thick

Tread: Nylon nº 30.

Standard: NBR ISO 20345:2015.

Sizes: from 33 to 47.

Warranty: 36 months

Color: Brown

Approval Certificate: 35719

Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Segmentos



Elétrica



Petrolífera



Petroquímica

Toe cap: Ultra-resilient polymer, withstanding 200J impact and compression up to 1500Kg (N) and 51% lighter than steel toe caps. It also has antimagnetic and anti-corrosive properties besides being undetectable by metal detectors.

Note: Class I insulating footwear has the purpose of insulation in low voltage electrical installations up to 500 V in dry conditions. The test voltage which is 14,000 V or 14 KV is the voltage under which the footwear is subjected to verification of its properties (the leakage current is verified).

Hygienic Insole: Anatomically conform in EVA antifungal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Non-metallic perforation resistant up to 1100N, made in multiple layers in fiber 100% polyester. Protecting all the plantar surface of the feet.

Single shoe weight: 0,636kg

Height leg: 230mm

Obs.: height leg is based on size 40 and it may vary 3,33 mm per size.

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)
- Sizes: L 345mm x W 595mm x H 536mm (collective box for up to 14 pairs)

Technologies



Composite TOE Comfortable, lightweight and impact-resistant composite non-metallic toe cap. withstanding 200J impact and compression up to 1500 N according to NBR ISO 20345/2015.



PAP Puncture-resistant, lightweight, non-metallic aramid fiber insole that covers 100% of the sole. Resistant to minimum drilling of 1100N according to NBR ISO 20344: 2015.



M MICRO High performance microfiber. Its texture is very similar to leather but it is washable, lighter and chemical resistant

Note: warranty begins from the date of production of the shoe