

# Line Premier Plus

## 75BPR29 CLI MP CPAP

Cód. Comercial: 700593 – CA 43791

Safety boots with composite toecap, padded collar padded collar, made of microfiber, lace-up closure, internal lining, torsion-resistant and two-density sole.



### Segments



Adventure



Production  
Area



Electric



Service  
Providers

### Technologies



TPU ANTI-TORSION insert applied to the sole shank, offering greater ankle support, stability on uneven terrain, when climbing stairs, and preventing accidents.



Injected PU insole, providing a perfect fit to the feet and greater comfort, preventing muscle fatigue. Its microporous surface allows for better sweat absorption and dissipation.



3D lining with Outlast PCM microcapsule coating. An intelligent system for rapid moisture dispersion and temperature regulation that adapts to the user's performance level.

### Shoe construction

**Sole** Made of two layers of polyurethane (PU), injected directly into the upper. (midsole) is softer and lighter, with a density of 0.4g/cm<sup>3</sup>, providing greater comfort; and the 2nd layer (sole) is more compact with a density of 1.0 g/cm<sup>3</sup>, resistant to abrasion with an anti-slip system made up of special grooves 3mm high and 6mm wide and slip-resistant on ceramic tile flooring, on ceramic and steel floors (SRC level).

**Polyamide thread no. 30**

**Trinforcement:** Termoplastic 1,5mm thick

**Upper** Made of microfiber M Micro with 17 to 19 thread thickness.

**Toe cap** Non-metallic, lightweight, and comfortable Composite toe cap, impact-resistant 200J and compression-resistant 1500N according to NBR ISO 20345/2015.

**Hygienic Insole** Soft Bed PU hygienic insole in injected PU, providing perfect fit and greater comfort, preventing muscle fatigue. Its micropore surface provides greater absorption and desorption of sweat.

**Mounting Insole** Resistant to non-metallic punctures of up to 1100N. up to 1100N, made of multiple layers of 100% polyester fibers. Protects the entire plantar surface of the foot.

**PU Bidensity numbering** 33 to 47

**Color** Black

### Technical Specification

**Requirement** NBR ISO 22010347:5

**Validity** 60 months

**Note:** The equipment's validity starts from the manufacturing date recorded on the shoe.

**Weight per shoe** 0.448kg

**Cuff Height** 137mm

**Note:** The cuff height is based on size 40 shoes and may vary by 3.33mm per size.

### Packaging

Sizes: L 345mm x W 28mm x H 13mm (Individual box)

Sizes: L 345mm x W 595mm x H 536mm (Collective box for up to 14 pairs)

For information about Marluvas footwear warranty, [CLICK HERE](#)

marluvas.com.br  
0300 788 3323

