

Kombat Line

95C32 BP

Cód. Comercial: 700749 – CA 41774

Occupational boot with composite toe cap, made of microfiber, lace closure, internal lining, side protection, and dual-density sole.



Applications



Production Area



Construction Area



General Services



Industrial Electrician

Footwear construction

Sole Consists of two layers of polyurethane (PU), directly injected into the upper, with the 1st layer (midsole) being softer and lighter, with a density of 0.4g/cm³ for greater comfort; and 2nd layer (outsole) more compact with a density of 0.9 g/cm³, resistant to cutting, piercing objects, and abrasion, with an anti-slip system consisting of special 3mm high and 6mm wide grooves.

Upper Smooth leather type with a thickness of 18 to 20 lines.

Thermoplastic counter with a thickness of 1.5mm

Polyamide stitching No. 30.

Vamp and Sweatband Lining Non-woven fabric with a minimum thickness of 1.9mm.

Plastic toe cap Injected in polypropylene, with a thickness of 1.5mm. Note: This type of toe cap does not have the same safety characteristics as a steel toe cap.

Assembly insole Stitched to the upper using the Strobel system, made of needled and resin-coated polyester, with a thickness of 2.0mm.

Hygienic insole Soft Comfort made of antifungal/antibacterial EVA, composed of microdots that provide sweat absorption and desorption.

Color Black

Sizes 33 to 47

Technical Information

Standard NBR ISO 20347:2015

Shelf Life 36 months

Note: The shelf life of the equipment begins from the manufacturing date engraved on the footwear

Weight per shoe 0.396kg

Boot Shaft Height 22.5cm

Note: height leg is based on size 40 and it may vary 3,33 mm per size

Packaging

Sizes: L 345mm x W 595mm x H 536mm (Collective box for up to 14 pairs)

Sizes: L 414mm x W 315mm x H 505mm (Collective box for up to 10 pairs)

Sizes: L 565mm x W 300mm x H 245mm (Collective box for up to 5 pairs)

[For information about shoes warranty click here](#)

marluvas.com.br
0300 788 3323

