



MARLUVAS

PROFESSIONAL EQUIPMENT

Kombat Line

50C32 C PET BROWN

Safety boot with composite toe cap, made of leather, entire upper, internal lining and dual density sole.



Technical Specification

- Composite toe cap
- Cowhide leather uppers
- Internal lining
- Antibacterial hygienic insole
- PU dual density sole

Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 0,9g/cm³, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and resistant to slipping on ceramic and steel floors (SRC Level).

Uppers: Smooth cowhide leather from 15 to 17 lines thick

Trinforcement: Termoplastic 1,5mm thick

Seam: Polyamide nº 30.

Standart: NBR ISO 20345:2015.

PU bidensity number: 35 to 47

Warranty: 36 months

Color: Brown

Approval Certificate: 42866

Upper and Strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap: Ultra-resilient polymer, withstanding 200J impact and compression up to 1500Kg (N) and 51% lighter than steel toe caps. It also has antimagnetic and anti-corrosive properties besides being undetectable by metal detectors.

Hygienic Insole: Anatomically conform in EVA antifungal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Upper sewed by strobel system, resin and needle-polyester - 2,0mm thick

Segmentos



Petrochemical business



Oil company

Single shoe weight: 0,636kg

Height Leg: 240mm

Note: height leg is based on size 40 and it may vary 3,33mm per size.

Product Package

Sizes: L 565mm x W 300mm x H 245mm

(collective box for up to 5 pairs)

Sizes: L 414mm x W 315mm x H 505mm

(collective box for up to 10 pairs)

Technologies



Hygienic insole with antibacterial properties composed of EVA and micro-stitches providing sweat absorption and desorption.



Composite TOE Comfortable, lightweight and impact-resistant composite non-metallic toe cap. withstanding 200J impact and compression up to 1500 N according to NBR ISO 20345/2015.

Note: warranty begins from the date of production of the shoe

For more Information about the warranty access our website marluvas.com.br/garantias