



MARLUVAS

PROFESSIONAL EQUIPMENT

Line Agriwork

55AG19-EC-LP

Occupational boot with side elastic closure, made of latigo leather with non-woven internal line.



Technical Specification:

- True-line toe cap
- Uppers in rust colored latigo leather
- Internal lining
- Antibacterial hygienic Insole
- PU dual density Sole

Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 0,9 g/cm³, abrasion resistant with antislip system made up of special grooves, 3mm height and 6mm width and slip resistance on ceramic steel floor (SRC level).

Uppers: Rust colored latigo leather 14 to 16 lines

Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap True-line = Cytoplasmic activated at 200 °C, hot applied by fusing it to the uppers, 0.9mm thickness.

Trinforcement: Termoplastic thick 1,5mm

Tread: Polyamide nº 30

Requirement: NBR ISSO 20347-2015

Size: PU dual density from 34 to 47

Warranty: 36 months

Color: Rust

Approval Certificate: 42020

Segments



Agricultural



Administrative Areas



Service Provider

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Upper sewed by strobels system, resin and needle-polyester- 2,0mm thick.

Single shoe weight: 0,310kg

Height leg: 122mm

Ps.: height leg is based on size 40 and it may vary 3,33 mm per size.

Product Package:

Sizes: L 340mm x W 28 mm x H 13mm (individual box)

Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

Tecnologias



Air confort woven made of polyester fibers that ensure greater softness, lightness and convenience to users

Note: warranty begins from the date of production of the shoe