

Line Kombat

70C32 C PET

Commercial Code: 700394 – CA: 41083

Safety boot with composite toe cap, made of microfiber, full closure, internal lining and dual-density outsole.




Segments



Petroleum



Electrical



Petrochemical

Footwear Construction

Outsole: Dual-density polyurethane (PU), injected directly onto the upper.

- 1st layer (midsole): lighter, density 0.4 g/cm³, providing comfort.
- 2nd layer (sole): more compact, density 1.0 g/cm³, resistant to cuts, punctures, and abrasion.
- Anti-slip system for ceramic floors and steel floors (SRC level).

Upper: Made of MMicro microfiber with thickness from 17 to 19 lines.

Color: Brown / White

Sizes: 33 to 47

Vamp and quarter lining: Non-woven short-fiber fabric with minimum thickness of 1.9 mm.

Toe cap: Composite (non-metallic), supports impacts up to 200 J and compression up to 1500 kg (N), approximately 51% lighter than steel and not detectable by metal detectors.

Strobel insole: Polyester resin-coated with thickness of 2.0 mm.

Anatomical hygienic insole in EVA, antifungal/antibacterial, with absorption micropoints.

Counterfort: Thermoplastic 1.5 mm

Technical Information

Approval NBR ISO 20345/2015.

Service life: 60 months

Weight per foot (size 40): approx. 0.606 kg

Boot height

Boot height: 240 mm

Average width: 3.33 mm per number above or below size 40

Packaging:

Individual box for 1 pair.

Approximate dimensions: 565 mm x 300 mm x 245 mm

[Para información sobre la garantía del calzado, haga clic aquí.](#)

marluvas.com.br

+55 (32) 3693-4000