

Vertentes Mais

Line

95S29 BP

Commercial Code: 700407 - C.A:41426

Safety shoe with polypropylene toe cap, padded collars, made of leather, lace closure, internal lining and dual density sole.



Segmentos



Production Area



Civil Construction



General Services



Service Providers

Footwear Construction

Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) - density 0,9g/cm³, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and resistant to slipping on ceramic and steel floors (SRC Level).

Uppers: Black relax leather from 15 to 17 lines thick

Color: Black

Sizes: From 33 to 47

Upper and strap Lining: Non-woven in short fibers with a minimum 1,9 thickness.

Trinforcement: Termoplastic 1,5mm thick

Toe cap: Polypropylene injected plastic, 1,5mm thick. P.S: this kind of toe cap does not have the same safety properties of the the steel cap.

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Upper sewed by strobel system, resin and needle-polyester - 2,0mm thick

Technical Specifications

Application NBR ISO 20347:2015

Warranty: 36 months

Note: The validity of the equipment begins from the manufacturing date stamped on the footwear.

Single shoe weight: 0,315kg

Height leg: 85mm

Obs.: height leg is based on size 40 and it may vary 3,33 mm per size

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

Note: warranty begins from the date of production of the shoe